

Outdoor central tube cables (maxibundle) with corrugated steel armouring A-DQ(ZN)(SR)2Y 4 - 24

CORNING

Features and Benefits

Dielectric strength elements

Aramid yarn

Corrugated steel tape

Protection against rodents and mechanical damage

UV and microbe resistant

Can be directly buried or installed in ducts


Fibres/buffer tubes colour coding to Telcordia-Bellcore

Easy identification of the individual tubes and fibres

The outdoor central tube (maxibundle) cables can be deployed both indoor and outdoor for campus backbone and building backbone (riser) cabling as well as for the cabling between floor distributors. The cables can be installed in conduits, ducts and be buried directly in the ground.


Standards

Waterblocking	Waterblocking according to IEC 60794-1-2-F5
Approval and Listings	Telcordia (Bellcore) colour standard for fibres and tubes



Outdoor central tube cables (maxibundle) with corrugated steel armouring A-DQ(ZN)(SR)2Y 4 - 24

CORNING



Specifications

Cable Design	
Fibre colouring	Blue, orange, green, brown, grey, white, red, black, yellow, violet, pink, turquoise
Buffer tube colour coding	Yellow (E9/125), Green (G50/125), Blue (G62.5L/125)
Buffer tube diameter	up to 12 fibres 3.0 mm, > 12 fibres 5.0 mm
Outer Jacket Material	Linear Low Density Polyethylene (LLDPE)
Outer Jacket Nominal Thickness	1.5 mm
Outer Jacket Colour	Black
Cable Marking	Metre - Handset - Sine - CORNING - Year - Cable type + Fibre count + Fibre type

Temperature Range	
Installation and Assembly	-5 °C to 50 °C
Operation	-20 °C to 60 °C
Storage	-25 °C to 70 °C

Outdoor central tube cables (maxibundle) with corrugated steel armouring A-DQ(ZN)(SR)2Y 4 - 24

CORNING

Mechanical Characteristics Cable

Fibre Count	Weight	Nominal Outer Diameter	Min. Bend Radius Installation	Min. Bend Radius Operation	Max. Tensile Strength for Installation	Crush Resistance (reversible)
4 - 12	60 kg/km	7.5 mm	150 mm	110 mm	1000 N	2000 N/10cm
24	93 kg/km	9.7 mm	195 mm	145 mm	1500 N	3000 N/10cm

* Fibre count per tube, colour coding of fibres and/or buffer tubes, hybrid construction, jacket colour and/or printings deviating from standard design have no influence whatsoever on mechanical and optical characteristics.

Chemical characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Transmission Performance

Multimode

Fibre Name	G50/125 ULTRA-BEND 7.5	G50/125 ULTRA-BEND 7.5	G50/125 ULTRA-BEND 7.5	G62.5L/125 InfiniCor® 300	E9/125 SMF28e+
Fibre Core Diameter (µm)	50	50	50	62.5	8.2
Fibre Category	OM4	OM3	OM2	OM1	OS2
Fibre Code	K	H	G	A	U
Wavelengths (nm)	850/1300	850/1300	850/1300	850/1300	1310/1383/1550
Maximum Attenuation (dB/km)	2.8/1.0	2.8/1.0	2.8/1.0	3.1/0.8	0.36/0.36/0.22
Typical attenuation (dB/km)	2.4/0.8	2.4/0.8	2.4/0.8	2.9/0.7	-
Serial 1 Gigabit Ethernet (m)	1100/600	1000/600	750/600	300/550	5000/-
Serial 10 Gigabit Ethernet (m)	550/-	300/333	150/-	33/-	10000/-/40000
Min. Overfilled Launch (OFL) Bandwidth (MHz*km)	3500/500	1500/500	700/500	200/600	-
Minimum Effective Modal Bandwidth (EMB) (MHz*km)	4700/-	2000/-	950/-	220/-	-
Induced attenuation @ 7.5 mm radius (dB)	<0.2/-	<0.2/-	<0.2/-	-	-
Cable cutoff wavelength (nm)	-	-	-	-	1260

Outdoor central tube cables (maxibundle) with corrugated steel armouring A-DQ(ZN)(SR)2Y 4 - 24

CORNING

Ordering Information | *Note: Contact Customer Service at 00800 2676 4641 for other options.*

F W C T 0 1 - S 0 0 - 0 0 3

1 2 3

1 Select fibre count.

004 = 4 fibres
006 = 6 fibres
008 = 8 fibres
012 = 12 fibres
016 = 16 fibres
024 = 24 fibres

2 Select fibre category.

A = 62.5 µm multimode, OM1
G = 50 µm multimode, OM2
H = 50 µm multimode, OM3
K = 50 µm multimode, OM4
U = Single-mode, OS2, SMF-28e®

4 Defines cable type.

003 = Outdoor armoured central tube (maxibundle) cable

*Maximum delivery length per drum is 4000 metres +3/-2% for Multimode fibres and 6000 metres +3/-2% for Single-mode fibres.

*Please notice that in the hybrid cables construction (different fibre types) the Multimode fibres are in sequence from the higher to the lower performance followed by the Single-mode fibres.

*For ordering information regarding non-standard design cables, please contact our Customer Service Centre. (See bottom of page for contact information.)



Corning Optical Communications GmbH & Co. KG · Leipziger Strasse 121 · 10117 Berlin, GERMANY
00 800 2676 4641 · FAX: +49 30 5303 2335 · www.corning.com/opcomm/emea

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/emea/trademarks. Corning Optical Communications is ISO 9001 and ISO 14001 certified. © 2014 Corning Optical Communications. All rights reserved.