

DATA SHEET

Item no.

Connector type

Frequency Range	10 - 3000 MHz
Impedance (Nom.)	75 Ω
Max DC Voltage	100 V
Transfer Impedance (CoMeT)	0,90 mΩ/m @ 5-30MHz
	0,03 mΩ/item @ 5-30MHz
Shielding Effectiveness(CoMeT)	133 dB @ 30-1000MHz
	125 dB @ 1000-3000MHz



All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
 Further technical specifications and installation instructions can be obtained on request.

Return Loss (IEC 61169-1)
 (RF Analyzer HP 8714C)

	Better than	Typical
10 - 500 MHz	-38 dB	-41,6 dB
500 - 860 MHz	-37 dB	-39,8 dB
860 - 1000 MHz	-36 dB	-38,9 dB
1000 - 1750 MHz	-26 dB	-29,0 dB
1750 - 2150 MHz	-20 dB	-23,3 dB
2150 - 3000 MHz	-17 dB	-20,3 dB

Insertion Loss Max.

	Better than	Typical
10 - 500 MHz	-0,11 dB	-0,06 dB
500 - 860 MHz	-0,13 dB	-0,08 dB
860 - 1000 MHz	-0,14 dB	-0,09 dB
1000 - 1750 MHz	-0,22 dB	-0,17 dB
1750 - 2150 MHz	-0,24 dB	-0,19 dB
2150 - 3000 MHz	-0,52 dB	-0,48 dB

Temperature
 Installing
 Operating
 Storing

-5° to +50° C
-40° to +70° C
-40° to +70° C

Intermodulation
 3rd Order (@2x+20dBm)

-150 dBc	+95 dBm
----------	---------

Inner Conductor Resistance
 (@ 1 A DC)

-

Sealing Test
 (IEC IP-code)

IP X8 1 meter / 24 hours

Insulation Resistance
 (@ 500 VDC)

>29,99 GΩ

O-rings

EPDM

Dielectric Strength
 DC Test Voltage

0,1 KV

Base Material

Body Parts	Brass CuZn39Pb3
Inner Conductor	Brass CuZn39Pb3 / Beryllium copper

Max. Tensile Strength
 Overall

-

Plating

Body Parts	Nitin-6
Inner Conductor	Gold / Tin / Nitin-6

Torsional Strength
 (Connector / Cable)

-

Insulators

PE

Test performed by
 Date of release

Troels V. Kristensen
August 6, 2008

Remarks

ISO 9001:2000 / ISO 14001 certified

Distributor: