

1. General Information

GPJ09-5817 is a series dome joint closure, basic on both mechanical and heatshrink base, closure body clamp and splice tray mounting bracket and tray. It can be apply for Aerial, wall mounting, direct burial application and so on.

2. Feature

- Capacity: 12-648C. 12F for each tray or 6F for each tray.
- Splice tray could be installed with splitter tray, each tray could be installed with 2 × 1:4 and 1 × 1:8 micro type splitter.
- Mechanical seal for the box, and heat shrink seal for cable ports. Good sealing performance.
- Many different types of splice tray as options.
- IP rate is IP68.

3. Specification

GPJ09-5817-A			
Dimension (mm)	370 × φ 270mm	Max. capacity (single fiber)	144F
Weight (kg)	5.5-6.2	Sealing type	Heat shrink
Ports	1 oval port 16 round port	Capacity of Tray (Single fiber) and max. Trays quantity	12C tray* 12 pcs 6C tray * 24 pcs
Uncut port(mm)	Φ 10~25mm		
Big branch port(mm)	4 pcs heat shrink port-- Φ 14~22mm 12 pcs heat shrink port -- Φ 8~16mm		

GPJ09-5817-B			
Dimension (mm)	505 × φ 270mm	Max. capacity (single fiber)	360F
Weight (kg)	7.5-8	Sealing type	Heat shrink
Ports	1 oval port	Capacity of Tray	12C tray* 30 pcs

	16 round port	(Single fiber) and max. Trays quantity	6C tray * 60 pcs
Uncut port(mm)	Φ 10~25mm		
Big branch port(mm)	4 pcs heat shrink port-- Φ 14~22mm 12 pcs heat shrink port -- Φ 8~16mm		

GPJ09-5817-C			
Dimension (mm)	625 × φ 270mm	Max. capacity (single fiber)	648F
Weight (kg)	9.5-12	Sealing type	Heat shrink
Ports	1 oval port 16 round port	Capacity of Tray (Single fiber) and max. Trays quantity	12C tray* 54 pcs 6C tray * 108 pcs
Uncut port(mm)	Φ 10~25mm		
Big branch port(mm)	4 pcs heat shrink port-- Φ 14~22mm 12 pcs heat shrink port -- Φ 8~16mm		

4. Product picture

4.1 Overall view



GPJ09-5817-A

GPJ09-5817-B

GPJ09-5817-C

4.2 Tray picture



4.3 Base picture

