


Item no.	99909909		Connector type	F-MINI-TD QM 4.5 SHORT W/O-RING	
			For cable	Bedeia, Telass BG 0,6_2,8C CUF-PVC	
Frequency Range	0.3 - 3000 MHz		Product photo		
Impedance (Nom.)	75 Ohm				
Amp. Rating (measured)	Cable data				
(calculated)	Cable data				
Transfer Impedance (CoMeT)	Class A				
	<5.0 mΩ/m @ 5-30MHz				
	<0.11 mΩ/item @ 5-30MHz				
Screening Attenuation(CoMeT)	Class A				
	>85 dB @ 30-1000MHz				
	>75 dB @ 1000-2000MHz				
	>65 dB @ 2000-3000MHz				
Return Loss (IEC 61169-1)	Better than	Typical	Insertion Loss Max.	Better than	Typical
0.3 - 500 MHz	-37 dB	-42.7 dB	0.3 - 500 MHz	-0.08 dB	-0.03 dB
500 - 860 MHz	-35 dB	-38.9 dB	500 - 860 MHz	-0.08 dB	-0.03 dB
860 - 1000 MHz	-33 dB	-37.4 dB	860 - 1000 MHz	-0.08 dB	-0.03 dB
1000 - 1750 MHz	-28 dB	-31.7 dB	1000 - 1750 MHz	-0.08 dB	-0.03 dB
1750 - 2150 MHz	-25 dB	-28.4 dB	1750 - 2150 MHz	-0.08 dB	-0.03 dB
2150 - 3000 MHz	-18 dB	-22.9 dB	2150 - 3000 MHz	-0.18 dB	-0.13 dB
Temperature			Intermodulation	IM3	
Installing	-5° to +50° C		3rd Order (@2x+20dBm)	-130 dBc	
Operating	-40° to +70° C		Inner Conductor Resistance	Cable data	
Storing	-40° to +70° C		(@ 1 A DC)		
Sealing Test			Insulation Resistance	Cable data	
(IEC IP-code)	IP X8 1 meter / 24 hours		(@ 500 VDC)		
O-rings	EPDM		Dielectric Strength	Cable data	
			DC Test Voltage		
Base Material			Max. Tensile Strength	Cable data	
Body Parts	Brass CuZn39Pb3		Overall	>10 Kgf	
Inner Conductor	Cable data			>98 N	
Plating			Torsional Strength	Cable data	
Body Parts	Nitin-6		(Connector / Cable)	* NATM	
Inner Conductor	Cable data		Test performed by	Søren B. Sørensen	
Insulators	Cabel data		Date of release	May 28, 2019	

Remarks * Not Able To Measure(NATM): The cable starts to twist without the connector losing its grip.

Connector designed according to the standard IEC 61169-24 (type F)
 All tests performed using instruments calibrated in accordance to our ISO 9001 certification.
 Further technical specifications and installation instructions can be obtained on request.